

# Integrity Clamp Covers<sup>TM</sup> EPDM

# **PRODUCT DESCRIPTION**

Integrity Products' Integrity Clamp Covers<sup>™</sup> are designed to make it quick and easy to seal protrusions around pipe clamps on insulated piping systems. These clamp covers are made from a high-performing EPDM rubber for extra protection against temperature, mechanical damage, weathering, and UV and ozone exposure. The task of trying to install cladding around pipe clamps on insulated piping systems has traditionally been very difficult—requiring an excessive amount of time from even a skilled tradesperson to complete! Now with Integrity Clamp Covers<sup>™</sup>, you can achieve a neat and tidy finish in a fraction of the time.

## **PRODUCT APPLICATION**

Integrity Products' Integrity Clamp Covers are a practical and cost-efficient solution to finish around pipe clamps on insulated piping systems. These covers enable a secure seal while featuring a drainage notch at the 6 o'clock position, allowing any moisture build-up to drain freely from the insulation system. The unique design of these Clamp Covers includes a radius that enables them to fit neatly onto the cladding. While installing this product, a bead of silicone is necessary on the flanged face of the Clamp Cover, ensuring not to silicone the drainage notch. The Clamp cover is then placed over the protrusion and secured onto the cladding using screws. Finally, a bead of silicone is required around the perimeter of the Clamp Cover to ensure a tight seal and minimize the risks of moisture ingress.

# MATERIAL SPECIFICATIONS

#### MATERIAL(S)

60 Durometer EPDM Rubber Cover/Cap

#### COLOR

Black

### CHEMICAL DEFINITION

Ethylene Propylene Diene Monomer UV RESISTANCE

Excellent

#### **OZONE RESISTANCE**

Excellent

#### WEATHER RESISTANCE

Excellent

**TENSILE STRENGTH** 

1600 PSI

#### ELONGATION

470%

TEMPERATURE RANGE

-58°F to 300°F (-50°C to 149°C) Constant Temperature

#### **OTHER SPECIFICATIONS**

ASTM D2000 Classification

# **PRODUCT SIZES** -

Various sizes available.

# **INSTALLATION**

Place Integrity Clamp Cover<sup>™</sup> over pipe clamp. Fix clamp cover with supplied machine screws. Run a small bead of silicone along the edge trim, screw holes, and around the perimeter of the installed Integrity Clamp Cover<sup>™</sup>.

integrity-products.com